



李順成塑膠工業有限公司

LEE SOON SENG PLASTIC INDUSTRIES SDN. BHD. (119117-M)

Lot 3304, Batu 24 1/2, Jalan Kulai-Air Hitam, 81000 Kulai, Johor Darul Ta'zim, Malaysia.

Tel : 07-6522288, 6522688 Fax : 07-6522299

http : //leesoonsengplastic.com/plastictray.com/apettray.com/pettray.com/thermoscancover.com E-mail : lss@lsspi.com

Material Safety Data Sheet

Manufacturer Name: Lee Soon Seng Plastic Industries Sdn. Bhd.	Product Name: PP Sheet Chemical Name: Polypropylene Sheet
Address: Lot 3304, Jalan Kulai-Air Hitam. Batu 24 1/2, 81000 Kulai. Johor. Malaysia	Contact No: Tel: +607-652 2288 Fax: +607-652 2299 Email: lss@lsspi.com

I. Product Identification

TITANPRO Polypropylene Homopolymer pellets

HMS*

Rating

Health hazard: 0 Minimal

(This MSDS is for all types, grades, and color of homopolymer pellets.)

Flammability hazard: 1 slight

Reactivity hazard: 0 Minimal

TSCA Registry: CAS #: 9003-07-0

Appearance and Color: Solid pellets, various color; odorless.

II. Hazardous Ingredients & Exposure Limits

As Lee Soon Seng Plastic Industries Sdn Bhd. interprets U.S. Occupational Safety and Health Act and Regulations, including the Hazard Communication Standard 29 CFR 1910.1200 date November 25, 1983, this product should NOT be considered hazardous material.

III. Typical Physical & Chemical Characteristics

Boiling point:	N/A	Solubility in water:	Negligible
Vapor pressure @ 20 °C:	N/A	Specific gravity:	0.88-0.92
Vapor density:	N/A	pH:	N/A
% volatile (vol):	<0.4	Evaporation rate:	N/A
Freezing/Melting point:	>160 °C (320 °F)		

IV. Fire Explosion & Reactivity Hazard Data

Flash Point: >329 °C (675 °F) Flammable limits: N/A

Autoignition temperature: >357 °C (675 °F)

Extinguishing media: Water spray, dry chemical, foam or carbon dioxide.

Special fire-fighting procedures: Standard procedures for class A fires.

Unusual fire & explosion hazard: None

Stability consideration: Stable.

- HJMS -- (Hazardous Material Identification System) Rating for the product as it is supplied.
- N/A -- Not applicable.

Incompatibility with: Avoid contact with strong oxidizing agents.

Hazardous decomposition products: None.





李順成塑膠工業有限公司

LEE SOON SENG PLASTIC INDUSTRIES SDN. BHD. (119117-M)

Lot 3304, Batu 24 1/2, Jalan Kulai-Air Hitam, 81000 Kulai, Johor Darul Ta'zim, Malaysia.

Tel : 07-6522288, 6522688 Fax : 07-6522299

http : //leesoonsengplastic.com/plastictray.com/apettray.com/pettray.com/thermoscancover.com E-mail : lss@lsspi.com

Hazardous products of combustion: Carbon dioxide, carbon monoxide.

Hazardous polymerization: will not occur.

V. Health Hazard Data

No known health hazards.

Emergency and First AID Procedures.

Molten Resin: If molten material come in contact with the skin, immerse under a running stream of water until cooled. DO NOT attempt to remove the resin from the skin. Removal can result in tissue damage. Get immediate medical attention.

VI. Disposal Material Procedures

Incineration of waste material in a permitted facility in accordance to local, state and federal regulation is the recommended disposal method. Land filling in a licensed facility in accordance to local, state and federal regulation is a suitable alternative.

VII. Applicable Control Measures

Personal protective equipment: Safety glasses

Work place: Eyewash fountains and safety shower should be easily accessible.

Handling and storage: Keep away from sparks and flame. This product may react with strong oxidizing agents and should not stored near such material.
precautions: Store in sprinkled warehouse. Keep temperature below 60 °C (140 °F) for quality control.

Lee Seen Seng Plastic Industries Sdn Bhd make no representations or warranties and there are no conditions with respect to the accuracy , reliability, or application to the information herein, its products or safety or suitability thereof, or result obtained, whether expressed or implied insultingly, without limitation, any implied warranty or merchantability or fitness for a particular purpose.

